

HI_SetBorderDistance

%HI_SetBorderDistance function

Funkcia

Function %HI_SetBorderDistance sets the size of the edges of windows controls.

Deklarácia

```
%HI_SetBorderDistance(  
  INT in _refId,  
  INT in _distLeft,  
  [, INT in _distTop  
  , INT in _distRight  
  , INT in _distBottom]  
)
```

Parametre

| | |
|--------------------|--|
| _refId | Reference to displayer (reference variable). |
| _distLeft | margin size left |
| _distTop | the optional margin size parameter upper, if not specified, _distLeft is used |
| _distRight | the optional margin size parameter right, if not specified, _distLeft is used |
| _distBottom | the optional margin size parameter bottom, if not specified, _distLeft is used |

Poznámka

Parameters _distTop, _distRight, _distBottom all or none must be entered.

Príklad

```
; margin  
%HI_SetBorderDistance(_RFID_BOX, 10, 5, 10, 5)  
%HI_SetBorderDistance(_RFID_BOX, 0, 0, 0, 0)  
  
; shortened  
%HI_SetBorderDistance(_RFID_BOX, 10) ; set all to 10  
%HI_SetBorderDistance(_RFID_BOX, 0) ; no margins
```



Related pages:

[Graphic object manipulation functions](#)
[Function arguments - types](#)