

# Application help (Access to the HI Process)

## Application help in D2000 system

D2000 system allows to use your own HTML help for D2000 system application instead of the standard D2000 help.

### Application help file

Name of application help file must be defined by one of the following ways:

1. ***application\_name\_LNG.chm***

Application help for individual language mutations. The **\_LNG** string defines the language mutation the application help is to be used for:

- **\_SK** - Slovak
- **\_CZ** - Czech
- **\_GB** - English

Example: Application help for English language mutation - *appl01\_GB.chm*

2. ***application\_name.chm***

Application help common for all D2000 language mutations.

Example: Application help - *appl01.chm*

Application help file(s) **MUST** be stored in the subdirectory **\Help** of the application directory !!!

**Note:**

D2000 system first searches the application help for respective language mutation (article 1) and if it does not exist then it searches the application help common for all language mutations (article 2).

### Use of application help

In D2000 system, you may define application help pages to be opened for objects of *Graph* and *Picture* type in the process **D2000 HI**. Pressing the **F1** key, if such an object has the focus, opens the application help page defined by the parameter **Help** in the configuration of corresponding object.

**Note:**

If the parameter **Help** is defined for picture, then the page of application help defined by the parameter is to be also open for all the object of *Picture*, *Graph* or *Report* types that are parts of the picture and no page of application help is defined for them (the parameter **Help** is empty string).

Example:

In the configuration of the graph *D.GrafAX05*, there is defined corresponding page of your application help in the parameter **Help**:

*html\graphAX05\_help.htm*

When the graph is opened in the process **D2000 HI**, then pressing the F1 key opens the application help on the given page.

If you want to open a page on specific place in a text (the condition is to use html attribute <a name>), use # character (bookmark in text) when you define the page.

*html\grafAX05\_help.htm#point1*

The page opens on place with the defined attribute <a name="point1">.

The application help can be set also in the picture script by the function **%HI\_SetPictureHelp**.