

# XML\_SaveDocument

## %XML\_SaveDocument function

|                    |   |          |                         |          |            |          |  |                    |   |
|--------------------|---|----------|-------------------------|----------|------------|----------|--|--------------------|---|
| Function           | The function saves the XML document to the specific file on the disk.   |          |                         |          |            |          |  |                    |   |
| Declaration        | <pre>BOOL %XML_SaveDocument(<br/>    INT in document,<br/>    TEXT in fileName[,<br/>    TEXT in encoding = "utf-8"]<br/>    [,BOOL in useProcInstruction]<br/>)</pre>  |          |                         |          |            |          |  |                    |   |
| Parameters         | <table><tr><td>document</td><td>Handle to XML document.</td></tr><tr><td>fileName</td><td>File name.</td></tr><tr><td>encoding</td><td>Encoding in which the document will be saved. You can use "utf-8" or "windows-1250".</td></tr><tr><td>useProcInstruction</td><td>Disables the displaying of the procedural instruction &lt;?xml version="1.0" encoding="xxx"?&gt;, where "xxx" defines encoding, which is in fact in the "encoding" parameter.</td></tr></table> | document | Handle to XML document. | fileName | File name. | encoding | Encoding in which the document will be saved. You can use "utf-8" or "windows-1250". | useProcInstruction | Disables the displaying of the procedural instruction <?xml version="1.0" encoding="xxx"?>, where "xxx" defines encoding, which is in fact in the "encoding" parameter. |
| document           | Handle to XML document.   |          |                         |          |            |          |  |                    |   |
| fileName           | File name.  |          |                         |          |            |          |  |                    |   |
| encoding           | Encoding in which the document will be saved. You can use "utf-8" or "windows-1250".  |          |                         |          |            |          |  |                    |   |
| useProcInstruction | Disables the displaying of the procedural instruction <?xml version="1.0" encoding="xxx"?>, where "xxx" defines encoding, which is in fact in the "encoding" parameter.   |          |                         |          |            |          |  |                    |   |
| Return value       | @TRUE - document saved, @FALSE - cannot save the document.  |          |                         |          |            |          |  |                    |   |
| Description        | The function saves the given XML document on the disk.  |          |                         |          |            |          |  |                    |   |
| Example            | <pre>BOOL _ok<br/>_ok := %XML_SaveDocument(_doc, "c:\data.xml")</pre>   |          |                         |          |            |          |  |                    |   |



Related pages:

- [XML file manipulation functions](#)
- [Function arguments - types](#)