

# XML\_ExportD2ObjToDocument

## %XML\_ExportD2ObjToDocument function

### Function

The function exports an object from configuration to an XML document.

### Declaration

```
INT %XML_ExportD2ObjToDocument(
    HBJ in objID,
    TEXT in eportSettings
)
```

### Parameters

<b>objID</b>	The value of HBJ or INT type which represents the unique identifier of object (HOBJ).
<b>exportSettings</b>	<a href="#">XML Export settings</a> (optional parameter) in form [setting={on/off} [setting={on/off} [...]]].

### Return value

Handle to the open XML document.

### Description

The function asks the [D2000 Server](#) process to export the object (according to unique identifier of the object (HOBJ) which has been entered by parameter objID) to XML documents. If specific object does not exist or the parameter represents an invalid value, the function will get back the invalid value.

### Example

```
INT _doc

_doc := %XML_ExportD2ObjToDocument(_hbj)
```

```
INT _doc

_doc := %XML_ExportD2ObjToDocument(Sec\HBJ, "zero_hobj=off exp_logs=on")
```

### Note

Error description can be called by means of the ESL function [%XML\\_GetLastErrorMessage](#) (if the function gets back the invalid value).



#### Related pages:

[XML file manipulation functions](#)  
[Function arguments - types](#)