

# DB\_TRANS\_CLOSE

## DB\_TRANS\_CLOSE action

Function	The action closes the <a href="#">Connection</a> to a database.		
Declaration	<div>DB_TRANS_CLOSE handleIdent_Int</div>		
Parameters	handleIdent_Int	out	<a href="#">Identifier</a> for an unique number (handle) of the <i>Connection</i> to a database.
Description	<p>The identifier for the <a href="#">Connection</a> number or handle comes from the execution of the <a href="#">DB_TRANS_OPEN</a> action.</p> <p>The action will terminate a connection. All changes, which are not confirmed by the action <a href="#">DB_TRANS_COMMIT</a> will be lost.</p> <p>All connections to tables, which originated (<a href="#">DB_CONNECT</a>, <a href="#">PG_CONNECT</a>, <a href="#">SQL_CONNECT</a>) within the frame of an terminating <i>Connection</i> to the database and are not closed yet, will be closed automatically.</p>		
Example	<a href="#">Database transactions.</a>		
Related topics	<div><a href="#">DB_TRANS_COMMIT</a> <a href="#">DB_TRANS_OPEN</a> <a href="#">DB_TRANS_ROLLBACK</a>  <a href="#">DB_CONNECT</a> <a href="#">DB_DELETE</a> <a href="#">DB_DISCONNECT</a> <a href="#">DB_INSERT</a> <a href="#">DB_INSUPD</a> <a href="#">DB_READ</a> <a href="#">DB_READ_BLOB</a> <a href="#">DB_UPDATE</a> <a href="#">DB_UPDATE_BLOB</a>  <a href="#">PG_CONNECT</a> <a href="#">PG_DISCONNECT</a> <a href="#">PG_READ</a> <a href="#">PG_INSERT</a> <a href="#">PG_DELETE</a> <a href="#">PG_UPDATE</a>  <a href="#">SQL_CONNECT</a> <a href="#">SQL_DISCONNECT</a> <a href="#">SQL_EXEC_DIRECT</a> <a href="#">SQL_EXEC_PROC</a>  <a href="#">SQL_PREPARE</a> <a href="#">SQL_BINDIN</a> <a href="#">SQL_FETCH</a> <a href="#">SQL_FREE</a></div> <p><a href="#">All database related actions.</a></p>		



Related pages:

[Script actions](#)