# DB_TRANS_CLOSE

## DB_TRANS_CLOSE action

**Function**

The action closes the *Connection* to a database.

**Declaration**

```
DB_TRANS_CLOSE handleIdent_Int
```

**Parameters**

| | | |
|---|---|---|
| handleIdent_Int | out | Identifier for an unique number (handle) of the *Connection* to a database. |

**Description**

The identifier for the *Connection* number or handle comes from the execution of the DB_TRANS_OPEN action.

The action will terminate a connection. All changes, which are not confirmed by the action DB_TRANS_COMMIT will be lost.

All connections to tables, which originated (DB_CONNECT, PG_CONNECT, SQL_CONNECT) within the frame of an terminating *Connection* to the database and are not closed yet, will be closed automatically.

**Example**

Database transactions.

**Related topics**

DB_TRANS_COMMIT
DB_TRANS_OPEN
DB_TRANS_ROLLBACK

DB_CONNECT
DB_DELETE
DB_DISCONNECT
DB_INSERT
DB_INSUPD
DB_READ
DB_READ_BLOB
DB_UPDATE
DB_UPDATE_BLOB

PG_CONNECT
PG_DISCONNECT
PG_READ
PG_INSERT
PG_DELETE
PG_UPDATE

SQL_CONNECT
SQL_DISCONNECT
SQL_EXEC_DIRECT
SQL_EXEC_PROC

SQL_PREPARE
SQL_BINDIN
SQL_FETCH
SQL_FREE

All database related actions.

**Related pages:**

Script actions