

# CNT\_DEBUG

## CNT\_DEBUG action

Declaration

CNT\_DEBUG \_hContainer [,"User ident string"]

Parameters

_hContainer	in	Unique identifier of <i>Int</i> type - <a href="#">data container</a> .
"User ident string"	in	String that is used in the debug information. It is defined by a user.

Description

This action ensures enabling/disabling of debug information in the particular *event.log* file when working with the [data containers](#).  
The data container is specified by a unique identifier - handle (*\_hContainer*) and has the user identifier "*text user ident*".

Debug information contains:

*"text user ident" ; \_handle'Img ; CNT\_AKCIA ; \_key*

The items are separated by semi-colon character ";".

**Begin of debug mode**  
-- CNT\_DEBUG \_handle, "text user ident"

**End of debug mode**  
-- CNT\_DEBUG \_handle

**Output:**

```
[15-02-2013 15:11:20] Debug CNT with handle : 1 and userIdent : TEST CNT1 :
Start
[15-02-2013 15:11:24] TEST CNT1; 1;CNT_INSERT;2
[15-02-2013 15:11:26] TEST CNT1; 1;Insert Caller CNT (IN OUT CNT_HANDLE);
[15-02-2013 15:11:27] TEST CNT1; 1;CNT_FIND;2
[15-02-2013 15:11:28] TEST CNT1; 1;Return Caller CNT;
[15-02-2013 15:11:31] Debug CNT with handle : 1 and userIdent : TEST CNT1:
Stop
```

Example

[Example: work with data container \(actions CNT\\_ ...\).](#)



Related pages:

[Script actions](#)