

OnPageChange

OnPageChange picture event

Declaration

Global handler:

```
ENTRY OnPageChange(IN INT _refId, IN INT _pageNr)
; script actions
END OnPageChange
```

Special handler:

```
ENTRY XXX_OnPageChange(IN INT _pageNr)
; script actions
END XXX_OnPageChange
```

Parameters

_refId	Parameter of INT type (required for global handler).
XXX	Name of Reference variable connected to graphic object (without the character "_").

Description

The picture event is being generated by the display of **Browser** type when the page is being changed. The value of the parameter **_pageNr** is the number of current page.

Example

The picture event handler of the display of **Browser** type with reference variable **_browser** displays new page number.

The **Browser** displays the structured variable **_rec**.

Special picture event handler:

```
ENTRY browser_OnPageChange(IN INT _pageNr)
TEXT _msg
_msg := "Page = " + %IToStr(_pageNr)
MESSAGE _msg ON _FROM_HIP
END browser_OnPageChange

BEGIN
REDIM _rec[10]
END
```

Global picture event handler:

```
ENTRY OnPageChange(IN INT _refId, IN INT _pageNr)
```

```
IF _refId = _browser THEN
```

```
; script actions
```

```
ENDIF
END OnPageChange
```



Related pages:

[Picture event handler](#)
[Picture events](#)