

# JSON\_ObjectSetObject

## %JSON\_ObjectSetObject function

Function	Adds a name-object pair into the JSON object						
Declaration	<pre>%JSON_ObjectSetObject(     INT in handle,     TEXT in field,     INT in object )</pre>						
Parameters	<table><tr><td>handle</td><td>Handle to parent JSON object.</td></tr><tr><td>field</td><td>Field name</td></tr><tr><td>object</td><td>Handle to JSON object</td></tr></table>	handle	Handle to parent JSON object.	field	Field name	object	Handle to JSON object
handle	Handle to parent JSON object.						
field	Field name						
object	Handle to JSON object						
Return value	None						
Description	<p>Function adds a name-object pair into the JSON object. If the field already exists, value is updated.</p> <p>Exception is thrown if handle to parent JSON object or added JSON object is invalid or field does not exists.</p>						
Example	<pre>INT _obj _obj := %JSON_CreateObject()  INT _arr _arr := %JSON_CreateArray()  %JSON_ArrayAppendValue(_arr, 3.1416) %JSON_ObjectSetArray(_obj, "Constants", _arr)  %JSON_FreeObjectHandle(_obj) %JSON_FreeArrayHandle(_arr)</pre>						



Related pages:

- [JSON format manipulation functions](#)
- [Function arguments - types](#)