


# Start parameters of DDE Server

When starting DDE Server, you can use the starting parameter. Exe form of process with the starting parameters is following:

```
d2dde.exe /parameter1 /parameter2 ... /parameterN
```

parameter	meaning
/AUTOLOGON	The program detects whether the function <i>autologon</i> of an operating system is active. If yes, the program tries to automatic logon to the information system by the mean of name and password for autologon of operating system. If it falls, a user has to logon.
/NOWINDOW	DDE Server is started without displaying of the main window. The logon dialog box occurs if necessary (if the automatic logon is not defined).
/TRACE	Enables the debugging. The buttons <b>Open Debug</b> and <b>Status</b> will be enabled in the dialog window.
/TRACELOG	Creates a log file with the log information.
/AN<Name>	See a description of the start parameter of processes - <a href="#">/AN&lt;Name&gt;</a> .
/AP<Password>	See a description of the start parameter of processes - <a href="#">/AP&lt;Password&gt;</a> .
/AF<Method>	See a description of the start parameter of processes - <a href="#">/AF&lt;Method&gt;</a> .
/W<Workstation>	See a description of the start parameter of processes - <a href="#">/W&lt;Workstation&gt;</a> .
/S<Server>	See a description of the start parameter of processes - <a href="#">/S&lt;Server&gt;</a> .
/F<Period>	See a description of the start parameter of processes - <a href="#">/F&lt;Period&gt;</a> .

 **Related pages:**  
[DDE Server - starting](#)