## Add a New Object to a Page (HI)

## Browser - add a new object to a page

You might add a D2000 system object to required page of the Browser using the following procedure:

- 1. Click corresponding button (1-6) to choose required page.
- 2. Click button Add object.
- 3. It opens a list of objects that allows to add selected objects into Browser intoBrowser intoBrowser into Browser into B


Select object for browser	7 3	Mask:			
All objects Diagnostika g04_Alarmy_1 nová logická skupina je to nová logická skupina je to OLD SELF1.CLC		Object name	Value type	Description	
Diagnostika	=	I SV.CNF_OBJECT_DEF	Struktura	Zoznam objektov	
gu4_Alarmy_ I	-	🔲 SV.g04_AA	Struktura	Popis objektu SV.AA	
nová logická skupina je to		E SV.g04_CPU_LOAD	Struktura	Popis premennej SV.CPU_LOAD	
		SV.g04_Export	Struktura		
SELF1.CLC		SV.MemoryReport	Struktura		
Pa Sys	-	I SV.TST_CAS	Struktura		
		🔳 SV.T_Funkcie	Struktura		
Historical Value	^	SV.T_KonfigProces	Struktura	Parametrické nastavenie proce	
🖓 I/O Tag		III SV.Vypocet	Struktura	Struktúra pre zátaz	
en ag Banga Line	Ξ	SVSystem_ArchivPerfor	Struktura	#D2_SV.System_ArchivPerfor	
Process	_	SVSystem_LinePerforma	Struktura	#D2_SV.System_LinePerforma	
😼 Remote Tag		📰 SVSystem_NetStatus	Struktura	#D2_SV.System_NetStatus#	
Station		SVSystem_OperSystem	Struktura		
Structured Variable	Ŧ	SVSystem_Proces	Struktura	#D2_SV.System_Proces#	

- 4. Select required object.
- 5. Click button Open object.

To find a particular object in the list is possible by mask or by filter (clicking on button ). By using filter the mask is blocked but the text is not deleted. Push the ENTER key or button to start searching.

The text from filter is deleted after clicking on button \*. The button is active only if filter contains some text.

Buttons placed in the corner right bottom determine the behaviour of the selection window after selecting an object:



The following window appears during insertion a structured variable into Browser to select row and column.

💷 S\	/Syst	em_ArchivPe	rformance	×
Row:	1	Column:	Name	•
			Cancel	ОК

The structured variable differs by brackets with two number defining row and column.

<b>]</b> + 🗈 🖬 🛣 🗙		23	4 5 6			
Object name	Value time	Value	Status	Units	Alarm	Description
E.GETARCHDATA	14:53:38.403 2/19/2010	0			NoAlarm	
SV.CNF_OBJECT_DEF[1]^ID	14:48:43.294 2/19/2010	Invalid			NoAlarm	Zoznam objektov
U.ARCHIV1	9:45:06.708 2/23/2009	DBA	Manual		NoAlarm	Meno instancie a
•		l.				۱.

The structured variable can be added also directly from picture.

<b>(</b> )	Related pages:
	Browser