## OnFetchDone

## OnFetchDone picture event

Declaration	Global handler is not defined. Special handler:		
	; sc:	Y XXX_OnFetchDone(RECORD (Structure definition) _rec, IN BOOL _bAfter) ript actions XXX_OnFetchDone	
Parameters	ххх	Name of Reference variable connected to displayer of Browser type.	
	_rec	Loaded page from the table.	
	_bAfter	Input parameter.	
	The picture event is being generated after fetching the data (page) into the displayer Browser type before the data are displayed (the parameter _ <i>bAfter=</i> @FALSE). The parameter _ <i>rec</i> contains the page loaded from the database. Within the picture event handler, it is possible to modify a value in the structure _ <i>rec</i> . After termination of the picture event processing, the value of the structure _ <i>rec</i> will be displayed in the Browser. After displaying, the picture event is again generated (_bAfter=@TRUE), but without possibility to change displayed data. When you handle the picture event, you can set currently selected line, appearance, The type of <i>Structure definition</i> must be equal to the type of the structure used by corresponding object of <i>Database Table</i> type, that is displayed in the Browser.		
Example Sp		pecial picture event handle:	
	; pic	ture event handler: Fetching the tab into Browser	
	; wit	h reference variable _browser assigned	
	ENTRY	browser_OnFetchDone(RECORD (SD.DbStruct) _rec, IN BOOL _bAfter)	
	END b	rowser_OnFetchDone	
	·		

