HI_SetPicturePos

%HI_SetPicturePos function

Function

The function sets the position of the picture either on the screen or on the desktop of the process D2000 HI.

Declaration

```
%HI_SetPicturePos(
   INT in x,
   INT in y,
   INT in _from := 0
 )
```

Parameters

x	Distance of the left picture margin from the left screen margin or the left desktop margin (according to the parameter *_from*).
y	Distance of the top picture margin from the top screen margin or the top desktop margin (according to the parameter *_from*).
from	Optional parameter. Possible values: • *0* - original (default) behaviour (see the article **Note**) • *1* - position on the screen • *2* - position on the desktop of the process **D2000 HI**

Note 1

Original (default) behaviour of the function (i.e. if the parameter *_from* is not defined or its value is 0).

The function sets the picture positions as follows:

A. for dialog or dialog modal picture windows

x	Distance of the left picture margin from the left screen margin.
y	Distance of the top picture margin from the top screen margin.

B. for other picture windows (so-called MDI picture windows)

x	Distance of the left picture margin from the left margin of the HI desktop.
y	Distance of the top picture margin from the top margin of the HI desktop.

Note 2

The functions are not designed for working with so-called dock pictures and for setting the positions of subpictures (i.e. pictures placed in picture).

Note 3

This function is available also in %HIX_ version.

Related pages:

Active picture manipulation functions
Function arguments - types