

HI_SetSelectedItem

%HI_GetSelectedItem, %HI_SetSelectedItem functions

| | | | | | | | | | | | |
|--------------------|---|--------------|---|----------------|-------------|--------------------|---|---------------|--|-----------------|--|
| Function | <p>The function %HI_SetSelectedItem sets the item of the Windows control of List box or Tree view types or the display of Browser type as current (selected) one (Control function).</p> <p>The function %HI_GetSelectedItem detects the index (from 1 ...) of the current (selected) item of the Windows control of List box or Tree view types or the display of Browser type.</p> | | | | | | | | | | |
| Declaration | <pre>%HI_SetSelectedItem(INT in refId, INT in itemIdx, BOOL in bInCurrPage := @FALSE BOOL in bState := @TRUE) INT %HI_GetSelectedItem(INT in refId, BOOL in bInCurrPage := @FALSE INT in iFromIdx := 0)</pre> | | | | | | | | | | |
| Parameters | <table border="1"><tr><td>refId</td><td>Reference to graphic object (reference variable).</td></tr><tr><td>itemIdx</td><td>Item index.</td></tr><tr><td>bInCurrPage</td><td>The parameter can be only used for display of Browser type:<ul style="list-style-type: none">• @TRUE - the parameter <i>itemIdx</i> defines the item index on currently displayed page of the Browser• @FALSE - the parameter <i>itemIdx</i> defines the item index regardless of the paging (within the frame of the entire Browser)</td></tr><tr><td>bState</td><td>The parameter can be only used for display of Browser type:<ul style="list-style-type: none">• @TRUE - the line is to be selected• @FALSE - the line is to be deselected</td></tr><tr><td>iFromIdx</td><td>The parameter can only be used if the browser is in multiselect mode - it sets the index, from which the selected line will be looked for. <i>Example:</i> If the selection comprises lines 1, 3 and 5 and the iFromIdx parameter is set to the value of 3, the function returns 5.</td></tr></table> | refId | Reference to graphic object (reference variable). | itemIdx | Item index. | bInCurrPage | The parameter can be only used for display of Browser type: <ul style="list-style-type: none">• @TRUE - the parameter <i>itemIdx</i> defines the item index on currently displayed page of the Browser• @FALSE - the parameter <i>itemIdx</i> defines the item index regardless of the paging (within the frame of the entire Browser) | bState | The parameter can be only used for display of Browser type: <ul style="list-style-type: none">• @TRUE - the line is to be selected• @FALSE - the line is to be deselected | iFromIdx | The parameter can only be used if the browser is in multiselect mode - it sets the index, from which the selected line will be looked for. <i>Example:</i> If the selection comprises lines 1, 3 and 5 and the iFromIdx parameter is set to the value of 3, the function returns 5. |
| refId | Reference to graphic object (reference variable). | | | | | | | | | | |
| itemIdx | Item index. | | | | | | | | | | |
| bInCurrPage | The parameter can be only used for display of Browser type: <ul style="list-style-type: none">• @TRUE - the parameter <i>itemIdx</i> defines the item index on currently displayed page of the Browser• @FALSE - the parameter <i>itemIdx</i> defines the item index regardless of the paging (within the frame of the entire Browser) | | | | | | | | | | |
| bState | The parameter can be only used for display of Browser type: <ul style="list-style-type: none">• @TRUE - the line is to be selected• @FALSE - the line is to be deselected | | | | | | | | | | |
| iFromIdx | The parameter can only be used if the browser is in multiselect mode - it sets the index, from which the selected line will be looked for. <i>Example:</i> If the selection comprises lines 1, 3 and 5 and the iFromIdx parameter is set to the value of 3, the function returns 5. | | | | | | | | | | |
| Note | <p>If no item is selected, the function %HI_GetSelectedItem returns the value of 0.</p> <p>For display of Tree view type, the parameter <i>itemIdx</i> is the unique identifier of the item.</p> <p>If the function %HI_SetSelectedItem is called on some item in Tree which is out of displayed area, the scrollbars will adjust automatically to see the selected item.</p> | | | | | | | | | | |



Related pages:

[Graphic object manipulation functions](#)
[Function arguments - types](#)