

HI_SetGraphButtons

%HI_SetGraphButtons function

Functions

The function **%HI_SetGraphButtons** sets the features of the user-defined buttons placed left to the description of the graphic flows in the displayer of [Graph](#) or [XY Graph](#) types ([Control function](#)).

Declaration

```
%HI_SetGraphButtons(  
    INT in refId,  
    INT in index,  
    INT in visible,  
    INT in enable  
)
```

Parameters

refId	Reference to displayer (reference variable).
index	Serial number of the graphic flow. Possible values: <ul style="list-style-type: none">• -1 - all buttons• 0 - button at the table header• 1 to n - button for particular graphic flow
visible	Button visibility. Possible values: <ul style="list-style-type: none">• 0 - no change• 1 - show• 2 - hide
enable	Enable / disable the button. Possible values: <ul style="list-style-type: none">• 0 - no change• 1 - enable the button• 2 - disable the button

Description


The function allows to show / hide and enable / disable the buttons placed left to the descriptions of graphic flows in the displayer of [Graph](#) or [XY Graph](#) types. If the button is enabled, clicking the button will generate the picture event [OnGraphBtnClick](#).

Show and enable the button for all graphic flows:

```
%HI_SetGraphButtons(_Graph, -1, 1, 1)
```

Example

In the displayer, there will be displayed the following button beside all graphic flows:



1 - user button



Related pages:

[Graphic object manipulation functions](#)
[Function arguments - types](#)