

HI_SetAlarmConfig

%HI_SetAlarmConfig function

Function

The function shows or hides individual parts of the [alarm list](#) in displayer of [Alarms](#) type.

Declaration

```
%HI_SetAlarmConfig(  
    INT in refId,  
    BOOL in showGroups,  
    BOOL in showLastEvents,  
    BOOL in showCrit,  
    BOOL in showUnCrit,  
    BOOL in showBlock  
)
```

Parameters	
refId	Reference to displayer (reference variable).
showGroups	Tree view of alarm groups. Possible values: <ul style="list-style-type: none">• @TRUE - show the tree view• @FALSE - hide the tree view
showLastEvents	List of last alarm events. Possible values: <ul style="list-style-type: none">• @TRUE - show the list• @FALSE - hide the list
showCrit	List of critical alarms. Possible values: <ul style="list-style-type: none">• @TRUE - show the list• @FALSE - hide the list
showUnCrit	List of uncritical alarms. Possible values: <ul style="list-style-type: none">• @TRUE - show the list• @FALSE - hide the list
showBlockd	List of blocked alarms. Possible values: <ul style="list-style-type: none">• @TRUE - show the list• @FALSE - hide the list



Related pages:

- [Graphic object manipulation functions](#)
- [Function arguments - types](#)