

HI_SetAXProp

%HI_GetAXProp, %HI_SetAXProp functions

Function	The function %HI_SetAXProp sets the given variable to the value defined by the parameter <i>value</i>. The function %HI_GetAXProp returns the value of the given variable.						
Declaration	<pre>%HI_SetAXProp(INT in refID, TEXT in variableName, in value) UNIVAL %HI_GetAXProp(INT in refID, TEXT in variableName)</pre>						
Parameters	<table><tr><td>refid</td><td>Reference to ActiveX object (reference variable) or interface returned by calling the function HI_GetAXProp.</td></tr><tr><td>variableName</td><td>Name of the variable to set/read.</td></tr><tr><td>value</td><td>Value (of required type) to set.</td></tr></table>	refid	Reference to ActiveX object (reference variable) or interface returned by calling the function HI_GetAXProp .	variableName	Name of the variable to set/read.	value	Value (of required type) to set.
refid	Reference to ActiveX object (reference variable) or interface returned by calling the function HI_GetAXProp .						
variableName	Name of the variable to set/read.						
value	Value (of required type) to set.						
Description	The function %HI_SetAXProp has no return value. The function %HI_GetAXProp returns the value of the variable.						
Example 1	In active picture, there is placed the ActiveX object of <i>Calendar Control 8.0</i> type. The following call <pre>%HI_SetAXProp(_AX_CAL, "Year", 2004)</pre> sets the year to 2004.						
Example 2	In active picture, there is placed the ActiveX object of <i>Calendar Control 8.0</i> type. The following call <pre>INT _i</pre> <pre>_i := %HI_GetAXProp(_AX_CAL, "Year")</pre> returns the current year defined in the ActiveX object.						



Related pages:

[ActiveX object manipulation functions](#)
[Function arguments - types](#)