

PG_INSERT

PG_INSERT action

Function

The action allows to insert a row into specified table.

Declaration

```
PG_INSERT handleIdent_Int, rowIdent, retCodeIdent_Int [ORAHINT  
hintIdent_Str]
```

Parameters

handleIdent_Int	in	Identifier of Int type (handle) of the connection with a table (returned by the action PG_CONNECT).
rowIdent	in	One structure row identifier (row to insert).
retCodeIdent_Int	out	Return value of Int type - action success.
hintIdent_Str	in	Expression of String type that defines Oracle SQL hint. It is used as an instruction for the performance optimizer of SQL command. The value is used without the opening and terminating characters /*<orahint>*/. The example is mentioned here .

Return code

The value of the parameter *transHandle_Int*. See the table of [error codes](#). It is possible to get [extended error information](#).

Description

Table must be opened with the access _DB_MODIFY. The type of the inserted row must be correct. Values of all items of the inserted row must be valid and the structure type of the local variable must be equal to the table type.

For using the function on Microsoft SQL Server platform, there must be defined the primary key or at least unique index for a table from the platform. For the platform Sybase and Oracle, the function works without these limitations.

Example

[Work with a database table \(actions PG_ ...\)](#).

Related topics

[DB_TRANS_OPEN](#)
[DB_TRANS_COMMIT](#)
[DB_TRANS_ROLLBACK](#)
[DB_TRANS_CLOSE](#)

[PG_CONNECT](#)
[PG_DISCONNECT](#)
[PG_READ](#)
[PG_DELETE](#)
[PG_UPDATE](#)

[All database related actions](#).



Related pages:

[Script actions](#)