

LOGEX

LOGEX action

Function	Log the text into the log database.										
Declaration	LOGEX strExpression [LINENO] [PRIORITY prtyExpr_Int]										
Parameters	<table><tr><td>str Exp res sion</td><td>in</td><td>Expression of <i>String</i> type - its value will be written into log database (the column Incident). Maximum characters: 200 (a text is cropped from the right).</td></tr><tr><td>LIN ENO</td><td>in</td><td>Optional key word. If it is entered, the script line which the action is placed in is to be written to the log database (the column Incident).</td></tr><tr><td>prty Exp r_Int</td><td>in</td><td>Expression of Int type that determines a priority of storing the log into the log database. Its value must be within the range of _LOG_PRTY_INFO (0) .. _LOG_PRTY_ERROR(5). If it is not, the action generates the error _ERR_RANGE_ERROR.</td></tr></table>		str Exp res sion	in	Expression of <i>String</i> type - its value will be written into log database (the column Incident). Maximum characters: 200 (a text is cropped from the right).	LIN ENO	in	Optional key word. If it is entered, the script line which the action is placed in is to be written to the log database (the column Incident).	prty Exp r_Int	in	Expression of Int type that determines a priority of storing the log into the log database. Its value must be within the range of _LOG_PRTY_INFO (0) .. _LOG_PRTY_ERROR (5). If it is not, the action generates the error _ERR_RANGE_ERROR .
str Exp res sion	in	Expression of <i>String</i> type - its value will be written into log database (the column Incident). Maximum characters: 200 (a text is cropped from the right).									
LIN ENO	in	Optional key word. If it is entered, the script line which the action is placed in is to be written to the log database (the column Incident).									
prty Exp r_Int	in	Expression of Int type that determines a priority of storing the log into the log database. Its value must be within the range of _LOG_PRTY_INFO (0) .. _LOG_PRTY_ERROR (5). If it is not, the action generates the error _ERR_RANGE_ERROR .									
Description	The action will perform a log into the log database. Text is characterized by value of expression <i>strExpression</i> (in contrast to LOG action).										
Example	BEGIN REAL _temperature _temperature := 1.123 LOGEX "Temperature=" + %IToStr (_temperature) PRIORITY _LOG_PRTY_CRITALARM END										



Related pages:

[Script actions](#)
[LOG](#)
[READLOG](#)