CNT_DEBUG

CNT_DEBUG action

Declaration

```
CNT_DEBUG _hContainer [,"User ident string"]
```

Parameters

_hContainer	in	Unique identifier of *Int* type - data container.
"User ident string"	in	String that is used in the debug information. It is defined by a user.

Description

This action ensures enabling / disabling of debug information in the particular *event.log* file when working with data container.
Data container is specified by a unique identifier - handle (*_hContainer*) and has the user identifier "*text user ident*".

Debug information contains:

"text user ident" ; _handle'Img ; CNT_AKCIA ; _key

The items are separated by semi-colon character ";".

Begin of debug mode
-- CNT_DEBUG _handle, "text user ident"

End of debug mode
-- CNT_DEBUG _handle

Output:

```
[15-02-2013 15:11:20] Debug CNT with handle :  1 and userIdent : TEST CNT1 :
Start
[15-02-2013 15:11:24] TEST CNT1; 1;CNT_INSERT;2
[15-02-2013 15:11:26] TEST CNT1; 1;Insert Caller CNT (IN OUT CNT_HANDLE);
[15-02-2013 15:11:27] TEST CNT1; 1;CNT_FIND;2
[15-02-2013 15:11:28] TEST CNT1; 1;Return Caller CNT;
[15-02-2013 15:11:31] Debug CNT with handle :  1 and userIdent :  TEST CNT1:
Stop
```

Example

Example: work with data container (actions CNT_ ...).

Related pages:

Script actions