

DBS_* for Database Access

DBS_* actions for table access

The group of actions DBS_READ, DBS_DELETE, DBS_INSERT, DBS_UPDATE are intended to work with a table. They are other than the actions [DB_READ](#), [DB_DELETE](#), [DB_INSERT](#), [DB_UPDATE](#), because they don't require opening a table before (calling the action [DB_CONNECT](#)).

All parameters of the DBS_* actions are identical with the parameters of the DB_* actions, except the first parameter. The first parameter of the actions DB_* is always the handle to a table that is acquired when opening the table using the DB_CONNECT action. For the DB_* actions, this parameter is [substituted by the reference](#) to a [Database table](#) type object.

An advantage of the DBS_* actions when working with a table is the possibility to leave out closing and opening the table (a shorter declaration). On the other hand, a disadvantage is in the speed. Every calling a DBS_*action, within the frame of its handler in the process [D2000 DBManager](#), results in the need to open and then close the database (it may be a time-consuming operation) and represents, in terms of databases, relatively a nonstandard method. This method can be eliminated to a certain extent by an appropriate setting of the [optimization](#).

The need to open and close the database may be avoided in the scope of transaction processing, so that the command is followed by the parameter

```
TRANS
```

[_transHandle_Int](#), where [_transHandle_Int](#) is the identifier of the [Connection](#) to a database.



Related pages:

[Script actions](#)