

SQL_FREE

SQL_FREE action

Function	The action closes (finishes) reading initialized by the action SQL_PREPARE.
Declaration	SQL_FREE
Parameters	handleIdent_Int handleIdent_Int in Identifier - the unique number (handle) of a connection.
Description	The action allows to release the OS resources used by particular process D2000 DBManager to execute the action SQL_PREPARE. If the action is not used, it will be executed automatically after the script termination or after using the action SQL_DISCONNECT.
Example	Work with a database (actions SQL_...). <pre>INT _handle ; handle to database INT _retCode ; return code TEXT _name ; product name TEXT _type ; product type SQL_CONNECT MyDatabase, _handle, _retCode SQL_PREPARE _handle, _retCode, _sqlNpar BIND _name, _type DO_LOOP SQL_FETCH _handle, _retCode EXIT_LOOP _retCode # _ERR_NO_ERROR ; data processing goes here END_LOOP SQL_FREE _handle SQL_DISCONNECT _handle</pre>
Related topics	DB_TRANS_OPEN DB_TRANS_COMMIT DB_TRANS_ROLLBACK DB_TRANS_CLOSE SQL_CONNECT SQL_DISCONNECT SQL_EXEC_DIRECT SQL_EXEC_PROC SQL_PREPARE SQL_BINDIN SQL_FETCH SQL_SELECT All database related actions.



Related pages:

[Script actions](#)