

HI_GetPicturePos

%HI_GetPicturePosX, %HI_GetPicturePosY functions

Function

The functions return the positions of the picture on the screen or on the desktop of the process [D2000 HI](#).

Declaration

```
INT %HI_GetPicturePosX(  
    [INT in _from := 0]  
)  
  
INT %HI_GetPicturePosY(  
    [INT in _from := 0]  
)
```

Parameters

_from	Optional parameter. Possible values: <ul style="list-style-type: none">• 0 - original (default) behavior (see the article Note 1)• 1 - position on the screen• 2 - position on the desktop of D2000 HI
--------------	--

Example

The function **%HI_GetPicturePosX** returns the distance of the left picture margin from the left screen margin, the function **%HI_GetPictureSizeY** returns the distance of the top picture margin from the top screen margin.

To set the picture size use the function [%HI_SetPicturePos](#).

```
INT _x  
INT _y  
  
_y := %HI_GetPicturePosX(1)  
_x := %HI_GetPicturePosY(1)
```

Note 1

Original (default) behavior of the functions (i.e. if the parameter *_from* is not specified or its value is 0).

The functions returns:

A) For [dialog](#) or [dialog modal](#) picture windows - positions on the screen.

B) For other picture windows (so-called [MDI](#) windows) - positions on the desktop of the process **D2000 HI**.

Note 2

The functions are not designed for working with so-called [dock](#) pictures.

Note 3

This function is available also in [%HIX_ version](#).



Related pages:

[Active picture manipulation functions](#)
[Function arguments - types](#)