

# OnPageChange

## OnPageChange picture event

Declaration

Global handler:

```
ENTRY OnPageChange(IN INT _refId, IN INT _pageNr)
; script actions
END OnPageChange
```

Special handler:

```
ENTRY XXX_OnPageChange(IN INT _pageNr)
; script actions
END XXX_OnPageChange
```

Parameters

_refId	Parameter of <b>INT</b> type (required for global handler).
<b>XXX</b>	Name of Reference variable connected to graphic object (without the character "_").

Description

The picture event is being generated by the displayer of **Browser** type when the page is being changed. The value of the parameter *\_pageNr* is the number of current page.

Example

The picture event handler of the displayer of Browser type with reference variable *\_browser* displays new page number.

The Browser displays the structured variable *\_rec*.

Special picture event handler:

```
ENTRY browser_OnPageChange(IN INT _pageNr)
TEXT _msg
_msg := "Page = " + %IToStr(_pageNr)
MESSAGE _msg ON _FROM_HIP
END browser_OnPageChange

BEGIN
REDIM _rec[10]
END
```

Global picture event handler:

```
ENTRY OnPageChange(IN INT _refId, IN INT _pageNr)

IF _refId = _browser THEN

; script actions

ENDIF
END OnPageChange
```



**Related pages:**

[Picture event handler](#)

[Picture events](#)