HI_GetCellToolTipTitle

%HI_SetCellToolTip, %HI_GetCellToolTipTitle, %HI_GetCellToolTipText functions

Function

Function **%HI_SetCellToolTip** sets the tooltip on the cell in displayer Browser. Tooltip consists of two texts - title and text.

Function **%HI_GetCellToolTipTitle** gets back the title of tooltip.

Function **%HI_GetCellTooltipText** gets back the text of tooltip.

Declaration

```
%HI_SetCellToolTip(
   INT in refId,
   INT in row,
   INT in col,
   TEXT in ttTitle,
   TEXT in ttText
 )

 TEXT %HI_GetCellToolTipTitle(
   INT in refId,
   INT in row,
   INT in col
 )

 TEXT %HI_GetCellToolTipText(
   INT in refId,
   INT in row,
   INT in col
 )
```

Parameters

refId	Reference to displayer (reference variable).
row	Row of the cell (in the range of 1...).
col	Column of the cell (in the range of 1...).
ttTitle	Title of the tooltip.
ttText	Text of the tooltip.

Example

```
;setting of the tooltip for cell [2,3]
```

```
%HI_SetCellToolTip (_browser, 2,3,  "Cell", "This is cell 2,3")
```

Related pages:

Graphic object manipulation functions
Function arguments - types