

HI_SetLogDBForObject

%HI_SetLogDBForObject function

Function	The function %HI_SetLogDBForObject sets the parameters for viewing data from the log database in displayer of <i>Logging</i> type (control function).																
Declaration	<div><pre>%HI_SetLogDBForObject(INT in refId, HBJ in refToObj, INT in priorityMask, BOOL in bASC, INT in pageLen, INT in intervalType)</pre></div> <div>or</div> <div><pre>%HI_SetLogDBForObject(INT in refId, HBJ in refToObj, INT in priorityMask, BOOL in bASC, INT in pageLen, TIME in bt, TIME in et)</pre></div>																
Parameters	<table><tr><td>refId</td><td>Reference to displayer of Logging type.</td></tr><tr><td>refToObj</td><td>Reference to object.</td></tr><tr><td>priorityMask</td><td>Event type filter.</td></tr><tr><td>bASC</td><td>Order:<ul style="list-style-type: none">• @True - ascending• @False - descending</td></tr><tr><td>pageLen</td><td>Page size within the interval of 5 ... 200.</td></tr><tr><td>intervalType</td><td>Time interval for browsing events. Possible values:<ul style="list-style-type: none">• 1 - last hour• 8 - last 8 hours• 12 - last 12 hours• 24 - last 24 hours</td></tr><tr><td>bt</td><td>Begin time (when you define own time interval for browsing events).</td></tr><tr><td>et</td><td>End time (when you define own time interval for browsing events).</td></tr></table>	refId	Reference to displayer of Logging type.	refToObj	Reference to object.	priorityMask	Event type filter.	bASC	Order: <ul style="list-style-type: none">• @True - ascending• @False - descending	pageLen	Page size within the interval of 5 ... 200.	intervalType	Time interval for browsing events. Possible values: <ul style="list-style-type: none">• 1 - last hour• 8 - last 8 hours• 12 - last 12 hours• 24 - last 24 hours	bt	Begin time (when you define own time interval for browsing events).	et	End time (when you define own time interval for browsing events).
refId	Reference to displayer of Logging type.																
refToObj	Reference to object.																
priorityMask	Event type filter.																
bASC	Order: <ul style="list-style-type: none">• @True - ascending• @False - descending																
pageLen	Page size within the interval of 5 ... 200.																
intervalType	Time interval for browsing events. Possible values: <ul style="list-style-type: none">• 1 - last hour• 8 - last 8 hours• 12 - last 12 hours• 24 - last 24 hours																
bt	Begin time (when you define own time interval for browsing events).																
et	End time (when you define own time interval for browsing events).																
Description	<p>The function parameters copy the behaviour of corresponding dialog box to open the log database when you browse events related to particular object.</p> <p>The parameter <i>priorityMask</i> represents the filter for Event type. It must be other than 0 and must be the sum of the values of the predefined variables <code>_LOG_PRTY_*</code>.</p>																
Example	<div><pre>%HI_SetLogDBForObject(_displayer, SystemD2000\HBJ, _LOG_PRTY_INFO, @TRUE, 20, 8)</pre></div>																

**Related pages:**[Graphic object manipulation functions](#)[Indexed local variables](#)[Function arguments - types](#)