

HI_SetBrowserBackColor

%HI_SetBrowserBackColor, %HI_GetBrowserBackColor functions

Function

The function **%HI_SetBrowserBackColor** sets the background color of the specified item of the display of [Browser](#) type ([Control function](#)).

The function **%HI_GetBrowserBackColor** returns the background color of the specified item of the display of [Browser](#) type.

Declaration

```
%HI_SetBrowserBackColor(  
    INT in refId,  
    INT in row,  
    INT in col,  
    INT in RGB  
)  
  
INT %HI_GetBrowserBackColor(  
    INT in refId,  
    INT in row,  
    INT in col  
)
```

Parameters

refId	Reference to graphic object (reference variable).
row	Item row (starting with 1...).
col	Item column (starting with 1...).
RGB	RGB index of color.

Note

To get the RGB index of a color use the function [%MakeRGB](#).

If the parameter *row* = 0, the color is set/detected for the whole column *col*.

If the parameter *col* = 0, the color is set/detected for the whole row *row*.

If both *row* = 0 and *col* = 0, then the color is set/detected for the whole display.

Example

```
; setting the background color to the whole display  
%HI_SetBrowserBackColor(_browser, 0, 0, _RGB)
```

```
; setting the background color for the column nr. 3  
%HI_SetBrowserBackColor(_browser, 0, 3, _RGB)
```

```
; setting the background color for the item [2,3]  
%HI_SetBrowserBackColor(_browser, 2, 3, _RGB)
```



Related pages:

[Graphic object manipulation functions](#)
[Function arguments - types](#)