

# DBS\_READ\_BLOB

## DB\_READ\_BLOB and DBS\_READ\_BLOB actions

### Function

Reading of one record of *LOB* type from the table in the database.  
*LOB* (Large OBject) can be:

- BLOB (Binary LOB),
- CLOB (Character LOB),
- XMLType (CLOB for work with xml data in Oracle DB).

### Declaration

```
DB_READ_BLOB handleIdent_Int, lobColNameIdent_Str, lobFileNameIdent_Str,  
retCodeIdent_Int, idKeyIdent [ORAHINT hintIdent_Str]  
  
DB_READ_BLOB handleIdent_Int, lobColNameIdent_Str, lobFileNameIdent_Str,  
retCodeIdent_Int WHERE strExpression_Str [ORAHINT hintIdent_Str]  
  
DBS_READ_BLOB dbObjIdent, lobColNameIdent_str, lobFileNameIdent_Str,  
retCodeIdent_Int, idKeyIdent [TRANS transHandle_Int] [ORAHINT  
hintIdent_Str]  
  
DBS_READ_BLOB dbObjIdent, lobColNameIdent_str, lobFileNameIdent_Str,  
retCodeIdent_Int WHERE strExpression_Str [TRANS transHandle_Int] [ORAHINT  
hintIdent_Str]
```

### Parameters

handleIdent_Int	in	Identifier of <i>Int</i> type (handle) of the connection to the database ( <a href="#">DB_CONNECT</a> ).
lobColNameIdent_Str	in	Name of a column of <i>LOB</i> type in the table.
lobFileNameIdent_Str	in	Name of a file, where the <i>LOB</i> type record read is to be written.
transHandle_Int	in	Identifier of the <a href="#">Connection</a> to the database.
idKeyIdent	in	Identification key determining the row (if the key consists of several columns, <i>idKeyIdent</i> is a structure of the same type as the table - just values of key columns are to be taken into account).
strExpression_Str	in	Expression of <i>String</i> type, that defines the table row read.
dbObjIdent	in	Reference to an object of <a href="#">Database table</a> type.
retCodeIdent_Int	out	Return code of <i>Int</i> type - action success.
hintIdent_Str	in	Expression of <i>String</i> type that defines Oracle SQL hint. It is used as an instruction for the performance optimizer of SQL command. The value is used without the opening and terminating characters /*+ <orahint> */. The example is mentioned <a href="#">here</a> .

### Return code

The value of the parameter *transHandle\_Int*. See the table of [error codes](#). It is possible to get [extended error information](#).

### Description

The action allows to read one record of *LOB* type from a table in a database. The table is defined either by the parameter *handleIdent\_Int*, which was got by previous calling the action [DB\\_CONNECT](#) or by the identifier *dbObjectIdent* representing an object of [Database Table](#) type. The 3rd and 4th types of the declarations is concerned to [DBS](#) actions, which do not require the explicit actions to open and close the database ([DB\\_CONNECT](#) and [DB\\_DISCONNECT](#)). Also it is possible to use the identifier running transaction *transHandle\_Int* gained by previous calling the action [DB\\_TRANS\\_OPEN](#).

The read record of *LOB* type is written into a file, which name is given in the parameter *lobFileNameIdent\_Str*. If the file already exists, then will be overwritten.

A value of the identifier *lobColNameIdent\_Str* defines a name of the column, which type is *LOB* and will be read.

A row, which will be read, can be defined:

1. Using the parameter *idKeyIdent*. An identification key must be defined in the configuration of an object of *Database table* type. Then a row, with a value matching the given identification key, will be found in the table.
2. By a value of the expression *strExpression\_Str*, that represents a clause WHERE for the SQL command SELECT executing a selection from the table.

The parameter *retCodeIdent\_Int* returns the attribute \_ERR\_NO\_ERROR - action success, or:

1. \_ERR\_FILE\_ERROR - an error occurred during operation with the file.
2. \_ERR\_NO\_DATA - if the record in the database is NULL.
3. Other default error codes.

#### Note

The action was tested for the file of 175 MB.

#### Example

[Work with a database table \(actions DB\\_ ...\)](#).

#### Related topics

[DB\\_CONNECT](#)  
[DB\\_DELETE](#)  
[DB\\_DISCONNECT](#)  
[DB\\_INSERT](#)  
[DB\\_INSUPD](#)  
[DB\\_READ](#)  
[DB\\_UPDATE](#)  
[DB\\_UPDATE\\_BLOB](#)  
  
[DB\\_TRANS\\_OPEN](#)  
[DB\\_TRANS\\_COMMIT](#)  
[DB\\_TRANS\\_ROLLBACK](#)  
[DB\\_TRANS\\_CLOSE](#)

[All database related actions.](#)



Related pages:

[Script actions](#)