

# Trieda BaseRunnable

Trieda je základnou bázovou triedou pre skripty v objektoch typu [Event](#) a [Schéma](#).

```
    public final void callESLSync(D2Process procIdent, SCallable pict, int instance, String procName,
D2Base... params) throws ExceptionRPCAbort, ExceptionRPCNotFound, ExceptionRPCNotRunning,
ExceptionRPCParameterError, ExceptionRPCRemoteException

    public final void callESLAsync(D2Process procIdent, SCallable pict, int instance, String procName,
D2Base... params)

    public final void callJavaSync(D2Process procIdent, SCallable pict, int instance, String procName,
D2Base... params) throws ExceptionRPCAbort, ExceptionRPCNotFound, ExceptionRPCNotRunning,
ExceptionRPCParameterError, ExceptionRPCRemoteException

    public final void callJavaAsync(D2Process procIdent, SCallable pict, int instance, String procName,
D2Base... params)

    public final byte[] sendByteArraySync(D2Process procIdent, SCallable pict, int instance, String
procName, byte[] byteArray) throws ExceptionRPCAbort, ExceptionRPCNotFound, ExceptionRPCNotRunning,
ExceptionRPCParameterError, ExceptionRPCRemoteException

    public final void sendByteArrayAsync(D2Process procIdent, SCallable pict, int instance, String procName,
byte[] byteArray)

    public final int getArchArr(D2Base archobj, int row, int col, D2SD dstValuesStr, int dstValueCol, D2SD
dstFlagsStr, int dstFlagsCol, Date startTime, Date endTime, int oversampleStep, int maxData)

    public final String getApplDir()

    public final String getInstallDir()

    public final SOUser getCurrentUser()

    public final D2Base getObjectByHOBj(int hobj)

    public final D2Base getObjectByName(String name)

    public final String valueToString(D2Base value, SOStatusText statusText)

    public final String valueToString(D2Base value, SOStatusText statusText, int idxTransPal)

    public final String valueToString(D2Base value, int idxTransPal)

    public final String lngTranslate(String str, int lngIdx)

    public void startTimer(ITimerListener listener, long intervalMS)
```



## Súvisiace stránky:

[Java ako skriptovací jazyk v systéme D2000](#)  
[Popis tried](#)