MODBUS Circutor CVMk

Circutor CVMk MODBUS communication protocol

Supported device types and versions Communication line configuration Communication station configuration I/O tag configuration Literature Changes and modifications Document revisions

Supported device types and versions

MODBUS RTU MASTER supports data reading from the Circutor CVMk analyzers.

Communication line configuration

- · Communication line category: Serial.
- Parameters of the asynchronous line depending on the design and type of device connection see literature about Circutor.

Communication station configuration

- Communication protocol: MODBUS Circutor CVMk.
- The station address is a number in the range of 0 up to 255 specified as a decimal number or as a hexadecimal number with a hash at the beginning (e.g. #1A).

Station protocol parameters

There can be defined the following parameters:

Table 1

Keyword	Full name	Meaning	Unit	Default value
RC	Retry Count	The number of request retries when an error in communication occurs.	-	2
RT	Retry Timeout	Delay between request retries if an error in communication occurs.	ms	200 millisec.
WFT	Wait First Timeout	First waiting for the response after sending a request.	ms	100 millisec.
WT	Wait Timeout	Delay between the readings of a response until it is completed.	ms	100 millisec.
MWR	Max Wait Retry	The number of response reading retries until the response is completed.	-	15

String with protocol parameters is written according to this rule:

Key_word=value;Key_word=value;...

Example:

RC=1;RT=500;

If a keyword with a valid value has not been found in the initial string, the default value is used according to Table 1.

I/O tag configuration

I/O tags: Ai

Address – a number in the range of 0 to 65535 – number of MODBUS double register. It can be specified as a decimal number or a hexadecimal number with a hash at the beginning (e.g. #0ABC).

The values are read by 2 registers and interpreted as a 4-byte integer. The addresses of values are described in the literature about Circutor.

Literature

_

Changes and modifications

Document revisions

• Ver. 1.0 – May 9, 2000 – the creation of the document



Related pages:

Communication protocols