DELETE (Script Actions)

DELETE action

Function

The action deletes one or more rows from local structured variable (i.e. local variable of *Record* type).

Declaration

```
DELETE _struct, rowIdx
```

or

```
DELETE _struct, rowFrom, rowTo
```

Parameters

_struct	in/out	Identifier of local variable of *Record* type.
rowIdx	in	Identifier of *Int* type - row to be deleted.
rowFrom, rowTo	in	Identifier of *Int* type.

Description

The first variant of the action deletes the row specified by the parameter *rowIdx* from the local variable defined by the parameter *_struct*. The value of the parameter *rowIdx* must be within the interval 1 ... *_struct\DIM*. For other value, the action will generate the error *_ERR_RANGE_ERROR*.

The second variant of the action deletes the rows within the range of <*rowFrom*, *rowTo*> from the local variable defined by the parameter *_struct.*

Example

```
RECORD (SD.RecordDef) _struct

 REDIM _struct[10]
 ; deleting the first row
 DELETE _struct, 1
```

Related pages:

Script actions

DELETE action

Function

The action deletes one or more rows from local structured variable (i.e. local variable of *Record* type).

Declaration

```
DELETE _struct, rowIdx
```

or

```
DELETE _struct, rowFrom, rowTo
```

Parameters

_struct	in/out	Identifier of local variable of *Record* type.
rowIdx	in	Identifier of *Int* type - row to be deleted.
rowFrom, rowTo	in	Identifier of *Int* type.

Description

The first variant of the action deletes the row specified by the parameter *rowIdx* from the local variable defined by the parameter *_struct*. The value of the parameter *rowIdx* must be within the interval 1 ... *_struct\DIM*. For other value, the action will generate the error *_ERR_RANGE_ERROR*.

The second variant of the action deletes the rows within the range of <*rowFrom*, *rowTo*> from the local variable defined by the parameter *_struct.*

Example

```
RECORD (SD.RecordDef) _struct

 REDIM _struct[10]
 ; deleting the first row
 DELETE _struct, 1
```

Related pages:

Script actions