

DB_TRANS_CLOSE

DB_TRANS_CLOSE action

Function	The action closes the Connection to a database.		
Declaration	<div>DB_TRANS_CLOSE handleIdent_Int</div>		
Parameters	<div>handleIdent_Int</div>	<div>out</div>	<div>Identifier for an unique number (handle) of the <i>Connection</i> to a database.</div>
Description	<p>The identifier for the Connection number or handle comes from the execution of the DB_TRANS_OPEN action.</p> <p>The action will terminate a connection. All changes, which are not confirmed by the action DB_TRANS_COMMIT will be lost.</p> <p>All connections to tables, which originated (DB_CONNECT, PG_CONNECT, SQL_CONNECT) within the frame of an terminating <i>Connection</i> to the database and are not closed yet, will be closed automatically.</p>		
Example	Database transactions.		
Related topics	<div>DB_TRANS_COMMIT DB_TRANS_OPEN DB_TRANS_ROLLBACK</div> <div>DB_CONNECT DB_DELETE DB_DISCONNECT DB_INSERT DB_INSUPD DB_READ DB_READ_BLOB DB_UPDATE DB_UPDATE_BLOB</div> <div>PG_CONNECT PG_DISCONNECT PG_READ PG_INSERT PG_DELETE PG_UPDATE</div> <div>SQL_CONNECT SQL_DISCONNECT SQL_EXEC_DIRECT SQL_EXEC_PROC</div> <div>SQL_PREPARE SQL_BINDIN SQL_FETCH SQL_FREE</div> <div>All database related actions.</div>		



Related pages:

[Script actions](#)