

OnSpin

OnSpin picture event

Declaration	Global handler:				
	<pre>ENTRY OnSpin(IN INT _refId) ; script actions END OnSpin</pre>				
	Special handler:				
	<pre>ENTRY XXX_OnSpin ; script actions END XXX_OnSpin</pre>				
Parameters	<table><tr><td>_refId</td><td>Parameter of the INT type (required for global handler).</td></tr><tr><td>XXX</td><td>Name of Reference variable connected to graphic object (without the character "_").</td></tr></table>	_refId	Parameter of the INT type (required for global handler).	XXX	Name of Reference variable connected to graphic object (without the character "_").
_refId	Parameter of the INT type (required for global handler).				
XXX	Name of Reference variable connected to graphic object (without the character "_").				
Description	The picture event is being generated when the user clicks on the Windows control of the Spin button type.				
Example	<p>Special picture event handler:</p> <pre>; picture event handler: Clicking the spin button ; with reference _Spin assigned</pre> <pre>ENTRY Spin_OnSpin</pre> <pre>; script actions END Spin_OnSpin</pre> <p>Global picture event handler:</p> <pre>; picture events handler: Clicking a spin button</pre> <pre>; with no special handler defined</pre> <pre>ENTRY OnSpin(IN INT _refId) ; _refId - value of reference local variable assigned to graphic object IF _refId = _Spin THEN ; test that determines the spin button ; the user clicked on ; script actions ENDIF END OnSpin</pre>				
Note	If both handlers are defined in picture script, the global handler will never be called for _refId=_Spin, because a special handler is already defined.				



Related pages:

[Picture event handler](#)

[Picture events](#)