

OnPageChange

OnPageChange picture event

Declaration	Global handler: <pre>ENTRY OnPageChange(IN INT _refId, IN INT _pageNr) ; script actions END OnPageChange</pre> Special handler: <pre>ENTRY XXX_OnPageChange(IN INT _pageNr) ; script actions END XXX_OnPageChange</pre>				
Parameters	<table><tr><td>_refId</td><td>Parameter of the INT type (required for global handler).</td></tr><tr><td>XXX</td><td>Name of Reference variable connected to graphic object (without the character "_").</td></tr></table>	_refId	Parameter of the INT type (required for global handler).	XXX	Name of Reference variable connected to graphic object (without the character "_").
_refId	Parameter of the INT type (required for global handler).				
XXX	Name of Reference variable connected to graphic object (without the character "_").				
Description	The picture event is being generated by the displayer of the Browser type when the page is being changed. The value of the parameter <i>_pageNr</i> is the number of current page.				
Example	The picture event handler of the displayer of Browser type with reference variable <i>_browser</i> displays new page number. The Browser displays the structured variable <i>_rec</i>. Special picture event handler: <pre>ENTRY browser_OnPageChange(IN INT _pageNr) TEXT _msg _msg := "Page = " + %IToStr(_pageNr) MESSAGE _msg ON _FROM_HIP END browser_OnPageChange BEGIN REDIM _rec[10] END</pre> Global picture event handler: <pre>ENTRY OnPageChange(IN INT _refId, IN INT _pageNr) IF _refId = _browser THEN ; script actions ENDIF END OnPageChange</pre>				