


OnGotFocus

OnGotFocus picture event

Declaration	<div>Global handler:</div> <div><pre>ENTRY OnGotFocus(IN INT _refId) ; script action END OnGotFocus</pre></div> <div>Special handler:</div> <div><pre>ENTRY XXX_OnGotFocus ; script action END XXX_OnGotFocus</pre></div>				
Parameters	<table><tr><td>_refId</td><td>Parameter of the Int type (required for global handler).</td></tr><tr><td>XXX</td><td>Name of the reference variable assigned to Windows control (without the character "_").</td></tr></table>	_refId	Parameter of the Int type (required for global handler).	XXX	Name of the reference variable assigned to Windows control (without the character "_").
_refId	Parameter of the Int type (required for global handler).				
XXX	Name of the reference variable assigned to Windows control (without the character "_").				
Description	The picture event is being generated when the Windows control (specified by its reference variable <i>_refId</i>) gets focus.				
Example	<div>Special picture event handler:</div> <div><pre>ENTRY List_OnGotFocus ; script actions END List_OnGotFocus</pre></div> <div>Global picture event handler:</div> <div><pre>ENTRY OnGotFocus(IN INT _refId) ; _refId - value of local reference variable ; assigned to Windows control IF _refId = 0 THEN ; no reference variable assigned ELSIF _refId = _editRefId THEN ; script actions ENDIF END OnGotFocus</pre></div>				
Note	If both handlers are defined in picture script, the global handler will never be called for <i>_refId=_List</i> , because special handler is already defined.				

 **Related pages:**

[Picture event handler](#)
[Picture events](#)