

HI_SetPicturePos

%HI_SetPicturePos function

Function

The function sets the position of the picture either on the screen or on the desktop of the process [D2000 HI](#).

Declaration

```
%HI_SetPicturePos(  
    INT in x,  
    INT in y,  
    INT in _from := 0  
)
```

Parameters

x	Distance of the left picture margin from the left screen margin or the left desktop margin (according to the parameter <i>_from</i>).
y	Distance of the top picture margin from the top screen margin or the top desktop margin (according to the parameter <i>_from</i>).
from	Optional parameter. Possible values: <ul style="list-style-type: none">• 0 - original (default) behaviour (see the article Note)• 1 - position on the screen• 2 - position on the desktop of the process D2000 HI

Note 1

Original (default) behaviour of the function (i.e. if the parameter *_from* is not defined or its value is 0).

The function sets the picture positions as follows:

A. for [dialog](#) or [dialog modal](#) picture windows

x	Distance of the left picture margin from the left screen margin.
y	Distance of the top picture margin from the top screen margin.

B. for other picture windows (so-called [MDI](#) picture windows)

x	Distance of the left picture margin from the left margin of the HI desktop .
y	Distance of the top picture margin from the top margin of the HI desktop .

Note 2

The functions are not designed for working with so-called [dock](#) pictures and for setting the positions of subpictures (i.e. pictures placed in picture).

Note 3

This function is available also in [%HIX_ version](#).



Related pages:

[Active picture manipulation functions](#)
[Function arguments - types](#)