

SaveTimeStamps

%SaveTimeStamps function

Function	Controlling function , which enables/disables change of the timestamp at setting the parameters of local values or objects in the D2000.		
Declaration	<pre>%SaveTimeStamps(BOOL in _bSaveTimeStamps)</pre>		
Parameters	<table><tr><td>bSaveTimeStamps</td><td> @TRUE - allows @FALSE- disallows Change of timestamp at assignment. </td></tr></table>	bSaveTimeStamps	@TRUE - allows @FALSE- disallows Change of timestamp at assignment.
bSaveTimeStamps	@TRUE - allows @FALSE- disallows Change of timestamp at assignment.		
Description	Controlling function, which enables/disables change of the timestamp at setting the parameters of local values or objects in the D2000. After script start preservation of timestamp is not activated. E.g. assignment executing:		
Example	<pre>INT _i _i := 1 + 1</pre> value 2 is set for local variable <code>_i</code> whereby real time is set for timestamp (e.g. <code>10:10:11 22-4-2008</code>). Following row disables timestamp actualization: <pre>%SaveTimeStamps(@FALSE)</pre> Following assignment sets new value (3) to the local variable without timestamp change. <pre>_i := 2 + 1</pre> This attribute is applied within inferences!!! E.g. by reading values from archive (action GETARCHARR) the read values from archive are assigned to the final column without affecting their timestamps!!!		



Related pages:

[ESL extended functions](#)
[Function arguments - types](#)