

HI_RefreshData

%HI_RefreshData function

Function

The function **%HI_RefreshData** ([Control functions](#)) may be used:

- for display of [Browser](#) type - it updates displayed data. It also allows to change the selection condition or sorting of data.
- for display of Report type (containing the report of [Crystal report](#) type) - it sets the values of parameters, for which the function [%HI_ReportPar](#) was called.

Declaration

```
%HI_RefreshData(
    INT in refId
    [, TEXT in whereStr
    [, TEXT in orderByStr
    [, in par1[, in par2[, ...]]]]]
)

BOOL %HI_RefreshDataSync(
    INT in refId
    [, TEXT in whereStr
    [, TEXT in orderByStr
    [, in par1[, in par2[, ...]]]]]
)
```

Parameters

refId	Reference to graphic object (reference variable).
whereStr	SQL condition WHERE for selection limit of displayed data (for Browser type only).
orderByStr	SQL command ORDER for selection order control (sorting) (for Browser type only)
par1, par2, ...	List of constants or local variables that will be used instead of the parameters of parameterized SQL condition.

Note

Condition and sorting can be also defined when you are configuring the graphic object in the process. These will be changed when the function **%HI_RefreshData** is called and displaying is updated. These parameters are not used for display of **Report** type.

The condition that has been changed by calling the function **%HI_RefreshData** may be [parameterized](#). The parameterization makes the work with SQL database easy because the preparing (compilation) of parameterized SQL expression can be done only when changing the condition or sorting (i.e. text format of SQL expression). The proper setting of database parameters (e.g. Oracle: `session_cached_cursors`) enables to recycling the cursors (the compiled commands) between the callings of **%HI_RefreshData**.

The rules for the parameters:

- parameter **refId** must be always valid,
- rules for **whereStr** and **orderByStr**:

	Entered valid	Empty or entered but invalid
whereStr	change of condition	The last entered condition is valid (if it has not been entered, there is an empty string).
orderByStr	change of sorting	The last entered sorting is valid (if it has not been entered, there is an empty string).

- if **par1** to **parN** are entered, their quantity must correspond to the condition (count #PAR#), however when changing the condition, they may not be omitted,
- if any of parameters from the range **par1** to **parN** is invalid, it means NULL.

The function **%HI_RefreshData** makes its action in the way that new conditions of display delivers to proper display and ends itself aside from a result or success of display.

The function **%HI_RefreshDataSync** waits on the selection according to new parameters and informs about the success of action by its value (@TRUE = successful execution, @FALSE = error). If the browser, which displays DB table, is configured so that it is initiated automatically (the parameter "[Initial query](#)" is ticked off), the function cannot be used in the initiate (BEGIN..END) part of the picture. In such case it returns @FALSE.

If a picture with a display of [Browser](#) type has been resized and the display has dynamic number of

lines depending on browser's height configured (see the parameter [Lines](#)), the function %
HI_RefreshData must be called to refresh the current page with a changed number of lines.

Example

```
%HI_RefreshData(_browser) ; updating (without changes in  
condition, sorting or parameters)  
%HI_RefreshData(_browser, "ID=21") ; changing the condition and  
updating  
%HI_RefreshData(_browser, "ID=21", "ID") ; changing the condition,  
sorting and updating
```

```
INT _cnt ; the local variable for the parameterized condition  
TEXT _name ; the local variable for the parameterized condition  
TEXT _INVALID = 1/0 ; auxiliary invalid constant of text type  
  
_cnt := 1  
_name := "%SELF%"  
  
; 1. change of condition (parameterized), sorting, parameters and updating  
%HI_RefreshData(_browser, "CNT=#PAR# AND NAME LIKE #PAR#", "NAME", _cnt,  
_name)  
  
_cnt := 2  
_name := "%ODBC%"  
  
; 2. just the change of parameters (recycling the SQL expression) and  
updating  
%HI_RefreshData(_browser, "CNT=#PAR# AND NAME LIKE #PAR#", "NAME", _cnt,  
_name) ;  
%HI_RefreshData(_browser, _INVALID, _INVALID, _cnt, _name) ; equivalent  
alternative to the writing by line above (if the condition has not been  
changed from the point 1)  
  
; 3. without changes (recycling the SQL expression) and updating  
%HI_RefreshData(_browser, "CNT=#PAR# AND NAME LIKE #PAR#", "NAME", _cnt,  
_name)  
%HI_RefreshData(_browser) ; equivalent alternative to the writing by line  
above (it the condition, sorting and parameters have not been changed from  
point 2)
```



Related pages:

[Graphic object manipulation functions](#)
[Function arguments - types](#)