

SQL_DISCONNECT

SQL_DISCONNECT action

Function

The action closes the connection (handle) to a database.

Declaration

```
SQL_DISCONNECT
```

```
handleIdent_Int
```

Parameters

handleIdent_Int	in	Identifier of the <i>Int</i> type (handle) - connection to a database (SQL_CONNECT).
-----------------	----	--

Description

Value of `handleIdent_Int` must be gained by using the action [SQL_CONNECT](#).

Example

[Work with a database \(actions SQL....\)](#).

```
INT _handle      ; handle to database
INT _retCode     ; return code
TEXT _name       ; product name
TEXT _type       ; product type
                ; parametrized SQL command
TEXT _sql = "SELECT Name, Type FROM Products WHERE ID>= #PAR# AND ID<=
#PAR#"

SQL_CONNECT MyDatabase, _handle, _retCode
SQL_PREPARE _handle, _retCode, _sql BINDOUT _name, _type
SQL_BINDIN _handle, _retCode, 1, 100 ; read all products between 1 and
100

DO_LOOP
    SQL_FETCH _handle, _retCode
    EXIT_LOOP _retCode # _ERR_NO_ERROR
    ; data processing goes here
END_LOOP

SQL_FREE _handle
SQL_DISCONNECT _handle
```

Related topics

[DB_TRANS_OPEN](#)
[DB_TRANS_COMMIT](#)
[DB_TRANS_ROLLBACK](#)
[DB_TRANS_CLOSE](#)

[SQL_CONNECT](#)
[SQL_EXEC_DIRECT](#)
[SQL_EXEC_PROC](#)

[SQL_PREPARE](#)
[SQL_BINDIN](#)
[SQL_FETCH](#)
[SQL_FREE](#)

[SQL_SELECT](#)

[All database related actions](#).



Related pages:

[Script actions](#)