

Script debugging (Eclipse development environment)

Eclipse - script debugging

To debug scripts in operation you have to start a process by running [Java Virtual Machine \(\(JVM\)\)](#) (which executes a script (EVENT.EXE/HI.EXE)) by the parameter "`--java-debug`". It activates JVM as a remote debugging. This parameter is an equivalent of "abbreviation" of the parameter entry "`---JVM-OPTION=-agentlib:jdwp=transport=dt_socket,server=y,address=8000,suspend=n`".

The debugging works in such a way that Eclipse connects to JVM on a defined port (default setting is port 8000, it may be changed by parameter "`address`") via TCP/IP protocol layer and executes debugging of the program.

****This holds:** the one JVM working on one computer can have a connection on one port. Hence, if you want to debug more pictures/events running on different EVENT.EXE/HI.EXE, you have to set different TCP/IP ports for each of the processes via the parameters from a command line.


For example:

```
hi.exe --JVM-OPTION=-agentlib:jdwp=transport=dt_socket,server=y,address=8000,suspend=n
event.exe --JVM-OPTION=-agentlib:jdwp=transport=dt_socket,server=y,address=8001,suspend=n
```


A debug configuration needs to be created in Eclipse if the process is in debug mode.

Follow these directions:


1. Open picture/event which is to be debugged (in our example it is S\$TEST1).




2. Choose the item **Debug configurations** from **Run** in the main menu, a dialog window opens, and then create a new debug configuration as Remote Java Application.




3. Insert the port number, it must be the same as it has been set at activating of event.exe/hi.exe (or it can be 8000 if a shortened parameter "--java-debug" was used). Click on **Debug** button.



4. Place breakpoint (1) on a required row.



5. Script executing stops on the row and you can debug (by buttons - 1), browse the values of the variables, ...



Note: You need not create the new configuration for the next debugging of the same script (steps 1, 2, 3).



Related pages:

[Java as a script language](#)

[Eclipse development environment](#)