

# SQL\_FREE

## SQL\_FREE action

Function

Declaration

Parameters

Description

Example

The action closes (finishes) reading initialized by the action SQL\_PREPARE.

handleIdent\_Int

handleIdent\_Int

in

Identifier - the unique number (handle) of a connection.

The action allows to release the OS resources used by a particular [D2000 DBManager](#) process to execute the action SQL\_PREPARE. If the action is not used, it will be executed automatically after the script termination or after using the action SQL\_DISCONNECT.

Work with a database (actions SQL\_...).

```
INT _handle      ; handle to database
INT _retCode     ; return code
TEXT _name       ; product name
TEXT _type       ; product type

SQL_CONNECT MyDatabase, _handle, _retCode
SQL_PREPARE _handle, _retCode, _sqlNpar BIND _name, _type

DO_LOOP
    SQL_FETCH _handle, _retCode
    EXIT_LOOP _retCode # _ERR_NO_ERROR
    ; data processing goes here
END_LOOP

SQL_FREE _handle
SQL_DISCONNECT _handle
```

Related topics

[DB\\_TRANS\\_OPEN](#)

[DB\\_TRANS\\_COMMIT](#)

[DB\\_TRANS\\_ROLLBACK](#)

[DB\\_TRANS\\_CLOSE](#)

[SQL\\_CONNECT](#)

[SQL\\_DISCONNECT](#)

[SQL\\_EXEC\\_DIRECT](#)

[SQL\\_EXEC\\_PROC](#)

[SQL\\_PREPARE](#)

[SQL\\_BINDIN](#)

[SQL\\_FETCH](#)

[SQL\\_SELECT](#)

[All database related actions.](#)



Related pages:

[Script actions](#)