

FIO_OpenAppend

%FIO_OpenAppend function

Function

Declaration

Parameters

Return value

Note

The function opens the specified file for writing at the end (appending).

```
INT %FIO_OpenAppend(  
    TEXT in fileName  
    [,BOOL in utf8 = @FALSE | ,TEXT in encoding = "@APP_DEFAULT@"]  
)
```

file Name	The name of the file to open.
utf8	An optional parameter of the <i>Boolean</i> type. If it is not written its alternate value is @FALSE . If the value is @TRUE , the file is supposed to be text-based and its content is encoded in UTF-8. When file encoded by UTF-8 is being read a possible BOM is omitted (characters 0xEF, 0xBB, 0xBF).
encoding	An optional parameter of the <i>Text</i> type. If it is not defined, its default value is "@APP_DEFAULT@". The list of supported encodings in ESL.

Zero - cannot open the file, nonzero - file opened.

The value of the parameter is used later when calling other **%FIO_*** functions, which need it. The value is valid within the ESL script instance, the function was called from.

Having finished the work with the file, it must be closed by calling the function [%FIO_Close](#). If the execution of ESL script is terminated early, the [D2000 EventHandler](#) process will automatically close all open files.



Related pages:

[ESL extended functions](#)
[Function arguments - types](#)