

# AddTime

## %AddTime function

Old name	%AddTimeT						
Function	The function adds the specified relative time <b>TimeB</b> to the specified absolute time <b>TimeA</b> . The result is absolute time.						
Declaration	<pre>TIME %AddTime(     TIME in TimeA,     REAL in TimeB,     TEXT in timeZone := %GetCurrentTimeZone() )</pre>						
Parameters	<table border="1"><tr><td>T i m eA</td><td>Absolute time.</td></tr><tr><td>T i m eB</td><td>Relative time.</td></tr><tr><td>ti m eZ o ne</td><td>Name of the time zone used for conversion to local time (e.g. "Europe/London") or definition of fixed offset from UTC using format "(+ -)hh[mi:ss]", where <i>hh</i> defines a number of hours, <i>mi</i> defines a number of minutes, and <i>ss</i> defines a number of seconds. Sign as well as a number of hours are mandatory parts of offset definition, number of minutes and seconds are optional and default to 0 (e.g. "+02:30" defines offset of 2 hours and 30 minutes from UTC). The empty text has the same meaning as function <a href="#">%GetCurrentTimeZone</a>. Note: For historical reasons, an integer parameter is also accepted. Its interpretation is as follows: 0 - zone "Europe/London", 3600 - zone "Europe/Bratislava", 7200 - zone "Europe/Kiev", 21600 - zone "Asia/Almaty". Usage of integer parameter is deprecated and generates warning into log file!</td></tr></table>	T i m eA	Absolute time.	T i m eB	Relative time.	ti m eZ o ne	Name of the time zone used for conversion to local time (e.g. "Europe/London") or definition of fixed offset from UTC using format "(+ -)hh[mi:ss]", where <i>hh</i> defines a number of hours, <i>mi</i> defines a number of minutes, and <i>ss</i> defines a number of seconds. Sign as well as a number of hours are mandatory parts of offset definition, number of minutes and seconds are optional and default to 0 (e.g. "+02:30" defines offset of 2 hours and 30 minutes from UTC). The empty text has the same meaning as function <a href="#">%GetCurrentTimeZone</a> . Note: For historical reasons, an integer parameter is also accepted. Its interpretation is as follows: 0 - zone "Europe/London", 3600 - zone "Europe/Bratislava", 7200 - zone "Europe/Kiev", 21600 - zone "Asia/Almaty". Usage of integer parameter is deprecated and generates warning into log file!
T i m eA	Absolute time.						
T i m eB	Relative time.						
ti m eZ o ne	Name of the time zone used for conversion to local time (e.g. "Europe/London") or definition of fixed offset from UTC using format "(+ -)hh[mi:ss]", where <i>hh</i> defines a number of hours, <i>mi</i> defines a number of minutes, and <i>ss</i> defines a number of seconds. Sign as well as a number of hours are mandatory parts of offset definition, number of minutes and seconds are optional and default to 0 (e.g. "+02:30" defines offset of 2 hours and 30 minutes from UTC). The empty text has the same meaning as function <a href="#">%GetCurrentTimeZone</a> . Note: For historical reasons, an integer parameter is also accepted. Its interpretation is as follows: 0 - zone "Europe/London", 3600 - zone "Europe/Bratislava", 7200 - zone "Europe/Kiev", 21600 - zone "Asia/Almaty". Usage of integer parameter is deprecated and generates warning into log file!						

Description

The function works as the function [%AddIntervalLocal](#).

Example

```
%AddTime(TM5, U.RTTime6)  
  
%AddTime(TM5, %StrToRelTime("256 17:03:16"))
```



Related pages:

[Implemented functions](#)  
[Function arguments - types](#)