

HI_SetBrowserFormatMask

%HI_SetBrowserFormatMask, %HI_GetBrowserFormatMask functions

Function The function **%HI_SetBrowserFormatMask** sets a [format mask](#) to the cell of [Browser](#) displayer. The function supports the basic mask syntax. From the extended syntax, it supports only {V}, {T} a {Tmask}.

The function **%HI_GetBrowserFormatMask** gets back a [format mask](#) that was set to the cell of [Browser](#) displayer.

Declaration

```
%HI_SetBrowserFormatMask(  
    INT in refId,  
    INT in row,  
    INT in col,  
    TEXT in formatMask  
)  
  
TEXT %HI_GetBrowserFormatMask(  
    INT in refId,  
    INT in row,  
    INT in col  
)
```

Parameters


refId	Reference to displayer (reference variable).
row	Row of the cell (from 1 up-to ...).
col	Column of the cell (from 1 up-to...).
formatMask	Value of Format mask .

Notes If the parameter *row* = 0, format mask will be set for the whole column *col*.
If the parameter *col* = 0, format mask will be set for the whole row *row*.
If both *row* and *col* = 0, format mask will be set for the whole displayer.

Example

```
; setting of format mask for the whole displayer  
%HI_SetBrowserFormatMask(_browser, 0, 0, "{V}")  
  
; setting of format mask for the column of No. 3  
%HI_SetBrowserFormatMask(_browser, 0, 3, "{V}")  
  
; setting of format mask for the cell [2,3]  
%HI_SetBrowserFormatMask(_browser, 2, 3, "{V}")
```

Note 2 This function is available also in [%HIX_ version](#).

 **Related pages:**

[Graphic object manipulation functions](#)
[Function arguments - types](#)