

OnBeforeEditItem

OnBeforeEditItem picture event

Declaration

Global handler:

```
ENTRY OnBeforeEditItem(IN INT _refId, IN INT _row, _col, RECORD (*STRUCTURE DEFINITION*) _rowData, BOOL _bAllowEdit)
      ; operations
END OnBeforeEditItem
```

Special handler:

```
ENTRY XXX_OnBeforeEditItem(IN INT _row, _col, RECORD (*STRUCTURE DEFINITION*) _rowData, BOOL _bAllowEdit)
      ; operations
END XXX_OnBeforeEditItem
```

Parameters

_refId	For global operation - mandatory input parameter of the Int. type.
XXX	Name of the Reference variable connected to the graphic object without the introductory sign "_".
_row, _col	Row, column of a cell of which value needs to be approved.
_rowData	Structure representing edited row.
_bAllowEdit	Output parameter - allowance indication of value editing.

Description

The event is generated by the displayer of the [Browser](#) type in the moment before the cell editing beginning. The cell is identified by its row (_row) and column (_col).

It is used when it is necessary to pre-fill the cell value in the editing window. In such case, a handler sets the cell in the _rowData parameter to the required value. This set value will be pre-filled for the user when starting to edit cells. Setting of the _rowData cell in a column different from _col is ignored.

If an event handler sets output parameter _bAllowEdit to the @FALSE value, the user will not be allowed to edit a cell.

If an event handler sets output parameter _bAllowEdit to the @TRUE value, the user will be allowed to edit a cell.

Example

In the example, there is a displayer event handler of the [Browser](#) type with the assigned reference variable _browser and connected structural variable of the SD.Params type that will pre-fill the item "Name".

```
ENTRY browser_OnBeforeEditItem(IN INT _row, IN INT _col, RECORD (SD.
Params) _rowData, BOOL _bAllowEdit)
      IF _row = 1 THEN
          _rowData[1]^Name:= "Name1"
      ENDIF
END browser_OnBeforeEditItem
```

Global picture event handler:

```
ENTRY OnBeforeEditItem(IN INT _refId, IN INT _row, IN INT _col, RECORD (SD.  
Params) _rowData, BOOL _bAllowEdit)  
    IF _refId = _browser THEN  
        IF _row = 1 THEN  
            _rowData[1]^Name:= "Name1"  
        ENDIF  
    ENDIF  
END OnBeforeEditItem
```



Related pages:

- [Picture event handler](#)
- [Picture events](#)