

# HI\_GetVisible

## %HI\_GetVisible, %HI\_SetVisible functions

Function	<p>The function <b>%HI_SetVisible</b> allows to hide/show the graphic object (<a href="#">Control function</a>).</p> <p>The function <b>%HI_GetVisible</b> detects whether the graphic object is visible.</p>				
Declaration	<pre>%HI_SetVisible(     INT in refId,     BOOL in bVisible )  BOOL %HI_GetVisible(     INT in refId )</pre>				
Parameters	<table><tr><td><b>refId</b></td><td>Reference to graphic object (<a href="#">reference variable</a>).</td></tr><tr><td><b>bVisible</b></td><td>@TRUE - show the graphic object. @FALSE - hide the graphic object.</td></tr></table>	<b>refId</b>	Reference to graphic object ( <a href="#">reference variable</a> ).	<b>bVisible</b>	@TRUE - show the graphic object. @FALSE - hide the graphic object.
<b>refId</b>	Reference to graphic object ( <a href="#">reference variable</a> ).				
<b>bVisible</b>	@TRUE - show the graphic object. @FALSE - hide the graphic object.				
Description	The function also allows to show / hide a tab of Windows control of <a href="#">Tab control</a> type - the parameter <i>refId</i> determines the reference variable name of the tab.				
Note 1	This function is available also in <a href="#">%HIX_ version</a> .				



Related pages:

- [Graphic object manipulation functions](#)
- [Function arguments - types](#)