


OnGotFocus

OnGotFocus picture event

| | | | | | |
|-------------|---|--------|---|------------|---|
| Declaration | <div>Global handler:</div> <div><pre>ENTRY OnGotFocus(IN INT _refId) ; script action END OnGotFocus</pre></div> <div>Special handler:</div> <div><pre>ENTRY XXX_OnGotFocus ; script action END XXX_OnGotFocus</pre></div> | | | | |
| Parameters | <table><tr><td>_refId</td><td>Parameter of Int type (required for global handler).</td></tr><tr><td>XXX</td><td>Name of the reference variable assigned to Windows control (without the character "_").</td></tr></table> | _refId | Parameter of Int type (required for global handler). | XXX | Name of the reference variable assigned to Windows control (without the character "_"). |
| _refId | Parameter of Int type (required for global handler). | | | | |
| XXX | Name of the reference variable assigned to Windows control (without the character "_"). | | | | |
| Description | The picture event is being generated when the Windows control (specified by its reference variable <i>_refId</i>) gets focus. | | | | |
| Example | <div>Special picture event handler:</div> <div><pre>ENTRY List_OnGotFocus ; script actions END List_OnGotFocus</pre></div> <div>Global picture event handler:</div> <div><pre>ENTRY OnGotFocus(IN INT _refId) ; _refId - value of local reference variable ; assigned to Windows control IF _refId = 0 THEN ; no reference variable assigned ELSIF _refId = _editRefId THEN ; script actions ENDIF END OnGotFocus</pre></div> | | | | |
| Note | If both handlers are defined in picture script, the global handler will never be called for <i>_refId=_List</i> , because special handler is already defined. | | | | |

 **Related pages:**

[Picture event handler](#)
[Picture events](#)