

DB_TRANS_CLOSE

DB_TRANS_CLOSE action

Function

The action closes the *Connection* to a database.

Declaration

```
DB_TRANS_CLOSE handleIdent_Int
```

Parameters

handleIdent_Int	out	Identifier for an unique number (handle) of the <i>Connection</i> to a database.
-----------------	-----	--

Description

The identifier for the *Connection* number or handle comes from the execution of the [DB_TRANS_OPEN](#) action.

The action will terminate a connection. All changes, which are not confirmed by the action [DB_TRANS_COMMIT](#) will be lost.

All connections to tables, which originated ([DB_CONNECT](#), [PG_CONNECT](#), [SQL_CONNECT](#)) within the frame of an terminating *Connection* to the database and are not closed yet, will be closed automatically.

Example

[Database transactions.](#)

Related topics

[DB_TRANS_COMMIT](#)
[DB_TRANS_OPEN](#)
[DB_TRANS_ROLLBACK](#)

[DB_CONNECT](#)
[DB_DELETE](#)
[DB_DISCONNECT](#)
[DB_INSERT](#)
[DB_INSUPD](#)
[DB_READ](#)
[DB_READ_BLOB](#)
[DB_UPDATE](#)
[DB_UPDATE_BLOB](#)

[PG_CONNECT](#)
[PG_DISCONNECT](#)
[PG_READ](#)
[PG_INSERT](#)
[PG_DELETE](#)
[PG_UPDATE](#)

[SQL_CONNECT](#)
[SQL_DISCONNECT](#)
[SQL_EXEC_DIRECT](#)
[SQL_EXEC_PROC](#)

[SQL_PREPARE](#)
[SQL_BINDIN](#)
[SQL_FETCH](#)
[SQL_FREE](#)

[All database related actions.](#)



Related pages:

[Script actions](#)