

# DBS\_UPDATE

## DB\_UPDATE and DBS\_UPDATE actions

### Function

Modification of the given existing row (rows) in the database.

### Declaration

```
DB_UPDATE handleIdent_Int, rowIdent, retCodeIdent_Int [WHERE  
strExpression_Str [BINDIN varIdent1, varIdent2, ... ]] [ORAHINT  
hintIdent_Str]  
  
DB_UPDATE handleIdent_Int, rowIdent, retCodeIdent_Int [WHERE  
strExpression_Str [BINDIN structRowIdent]] [ORAHINT hintIdent_Str]  
  
DBS_UPDATE dbObjIdent, rowIdent, retCodeIdent_Int [WHERE  
strExpression_Str [BINDIN varIdent1, varIdent2, ... ]] [TRANS  
transHandle_Int] [ORAHINT hintIdent_Str]  
  
DBS_UPDATE dbObjIdent, rowIdent, retCodeIdent_Int [WHERE  
strExpression_Str [BINDIN structRowIdent]] [TRANS transHandle_Int]  
[ORAHINT hintIdent_Str]
```

or

```
DB_UPDATE handleIdent_Int, structIdent, retCodeIdent_Int [ORAHINT  
hintIdent_Str]  
  
DBS_UPDATE dbObjIdent, structIdent, retCodeIdent_Int [TRANS  
transHandle_Int] [ORAHINT hintIdent_Str]
```

### Parameters

handl elident _Int	in	Identifier of <i>Int</i> type (handle) of the connection with the database ( <a href="#">DB_CONNECT</a> ).
dbObj Ident	in	Reference to an <a href="#">object</a> of <a href="#">Database table</a> type.
rowId ent	in	<a href="#">One structure row identifier</a> (a row to update).
structI dent	in	Identifier of entire structure (the rows to update).
retCo delde nt_Int	o ut	Return value of <i>Int</i> type - action success.
strEx pressi on_Str	in	Expression of <i>String</i> type, which identifies modified rows. If the expression is <a href="#">parameterized</a> , the keyword <b>BINDIN</b> and the values of parameters ( <i>structRowIdent</i> or <i>varIdent1</i> , <i>varIdent2</i> , ...) are mandatory.
varide nt1, varide nt2, ...	in	List of objects, constants or <a href="#">local variables</a> , which will specify the values of parameters of <a href="#">parameterized</a> SQL expression <i>strExpression_Str</i> .
struct RowI dent	in	Reference to a row of <a href="#">local variable</a> of <i>Record</i> type or to a row of <a href="#">structured variable</a> . The row's values will specify the values of parameters of <a href="#">parameterized</a> SQL expression <i>strExpression_Str</i> .
trans Hadle _Int	in	Identifier of the <a href="#">Connection</a> to the database.
hintId ent_S tr	in	Expression of <i>String</i> type that defines Oracle SQL hint. It is used as an instruction for the performance optimizer of SQL command. The value is used without the opening and terminating characters /*+ <orahint> */. The example is mentioned <a href="#">here</a> .

<b>Return code</b>	The value of the parameter <code>transHandle_Int</code> . See the table of <a href="#">error codes</a> . It is possible to get <a href="#">extended error information</a> .
<b>Description</b>	The database must be opened with the access <code>_DB MODIFY</code> . Analogous to the action <code>DB_READ (DBS_READ)</code> , modified rows may be determined by two ways: <ol style="list-style-type: none"> <li>Setting the key items in a structure row (<code>rowIdent</code>) or in the entire structure (<code>structIdent</code>). The setting must be performed before the action <code>DB_UPDATE</code>. The respective items must be marked as the key during the definition of an object of a <code>Table</code> type. Then in the database, a row which key items values are equal to the key items of <code>rowIdent</code> is found and is modified. The row or structure to be updated must be of a proper type of structure. The values of all key items in <code>rowIdent</code> must be valid, otherwise the update will fail, end with an error, and <code>%GetLastExtErrorCode()</code> will return error 667.</li> <li>The value of the expression <code>strExpression_Str</code> which represents <code>WHERE</code> clause for the SQL command <code>UPDATE</code> performing a database change. In this case, a key item value is not used.</li> </ol>

If the `strExpression_Str` expression is not specified (or is empty) or the key is not defined when defining a `Table` type object, the action will return the error `_ERR_TRANS_ERROR (11)` and the variable `_ERR_NR_TRANS_EX` will have the value `BAD_CONDITION`.

Note: we recommend using the version without the `strExpression_Str` expression - when using the expression, Oracle temporarily locks the updated table as well as all tables into which the updated table has foreign indexes. This can cause a blocked session if another transaction in progress has updated any rows in these tables. The blocking will last until the ongoing transaction is completed.

The advantage of the action `DBS_UPDATE` during the work with a table is the possibility to leave out its opening and closing (simpler notation).

**For D2000 v5.00:** A disadvantage of the action `DBS_UPDATE` is in speed. Each `DBS_UPDATE` call results in necessity to open and close the database in DBManager - it can be a time-consuming operation and it is a comparatively nonstandard method in term of databases. The need to open and close the database may be eliminated in the scope of transaction processing so that the command is followed by the parameter

```
TRANS
```

**For D2000 v6.00 and higher:** DBManager [optimization](#) (connection recycling, predefined connections) causes, that the action `DBS_UPDATE` is executes as quick as the action `DB_UPDATE` and moreover there is saved a time required for execution of the action `DB_CONNECT` to open the database.

The need to open and close the database may be eliminated in the scope of transaction processing so that the command is followed by the parameter

```
TRANS
```

## Example

[Work with a database table \(actions DB\\_ ...\).](#)

## Related topics

[DB\\_CONNECT](#)  
[DB\\_DELETE](#)  
[DB\\_DISCONNECT](#)  
[DB\\_INSERT](#)  
[DB\\_INSUPD](#)  
[DB\\_READ](#)  
[DB\\_READ\\_BLOB](#)  
[DB\\_UPDATE\\_BLOB](#)

[DB\\_TRANS\\_OPEN](#)  
[DB\\_TRANS\\_COMMIT](#)  
[DB\\_TRANS\\_ROLLBACK](#)  
[DB\\_TRANS\\_CLOSE](#)

[All database related actions](#)



Related pages:

[Script actions](#)

