

JSON Format Manipulation Functions

Functions available from D2000 V12.2.

JSON format manipulation functions allow creating, reading, writing and deleting JSON objects. Function names are created by the prefix `%JSON_`.

When adding invalid value (e.g. `%JSON_ObjectSetValue`), value in JSON is stored as `null`. When reading null value from JSON (e.g. `%JSON_ObjectGetValue`), value is interpreted as invalid value.

Every handle to JSON object or array must be released by calling `%JSON_FreeObjectHandle` or `%JSON_FreeArrayHandle`.

Handle remain valid also after deleting of child object or array (e.g. `%JSON_ArrayRemoveItem`) pointed to by the handle. Similarly when removed parent object or array, handle pointed to child remains valid.

Example:

```
INT _obj
INT _clientInfo
TEXT _d2version

_obj := %JSON_ObjectFromString(ModuleInfo)
_clientInfo := %JSON_ObjectGetObject(_obj, "client_data")

%JSON_FreeObjectHandle(_obj) ; release handle to _obj, _clientInfo is still valid handle

_d2version := %JSON_ObjectGetValue(_clientInfo, "d2000_version")

LOG "D2000 version", _d2version PRIORITY _LOG_PRTY_INFO

%JSON_FreeObjectHandle(_clientInfo) ; finally release _clientInfo handle
```

There is created JSON object from `ModuleInfo` variable, then we get value from object and this value is written into monitoring database.

%JSON file manipulation functions:

- `%JSON_CreateObject`
- `%JSON_CreateArray`
- `%JSON_FreeObjectHandle`
- `%JSON_FreeArrayHandle`
- `%JSON_ObjectSetValue`
- `%JSON_ObjectSetArray`
- `%JSON_ObjectSetObject`
- `%JSON_ArraySetValue`
- `%JSON_ArraySetArray`
- `%JSON_ArraySetObject`
- `%JSON_ArrayAppendValue`
- `%JSON_ArrayAppendArray`
- `%JSON_ArrayAppendObject`
- `%JSON_ObjectGetValue`
- `%JSON_ObjectGetArray`
- `%JSON_ObjectGetObject`
- `%JSON_ArrayGetValue`
- `%JSON_ArrayGetArray`
- `%JSON_ArrayGetObject`
- `%JSON_ObjectIsValue`
- `%JSON_ObjectIsArray`
- `%JSON_ObjectIsObject`
- `%JSON_ArrayIsValue`
- `%JSON_ArrayIsArray`
- `%JSON_ArrayIsObject`
- `%JSON_ArrayGetLength`
- `%JSON_ArraySetLength`
- `%JSON_ArrayClear`
- `%JSON_ArrayRemoveItem`
- `%JSON_ObjectGetFieldsCount`
- `%JSON_ObjectGetFieldName`
- `%JSON_ObjectHasField`
- `%JSON_ObjectClear`
- `%JSON_ObjectRemoveField`
- `%JSON_ObjectToString`
- `%JSON_ObjectFromString`
- `%JSON_ArrayToString`
- `%JSON_ArrayFromString`



Related pages:

[ESL extended functions](#)